

HOHUNET SERDESX PLATFORM

性能规格表

高性能交换硬件平台

文档版本：V3.1

发布日期：2026/01/04

平台简介

SerdesX平台是一个高性能、高密度的硬件交换平台，为人工智能应用提供高带宽网络支持。SerdesX平台支持100G/200G/400G/800G等多种端口形式，能够适应各种网络部署需求。

关键特性

- 丰富的网络虚拟化和智能无损网络特性，支持基于优先级的流量控制（PFC），显式拥塞通知（ECN）、跨设备链路聚合(MLAG)等
- 丰富的2层/3层协议
- 智能以太网OAM安全特性集

性能规格表

表 1：SerdesX平台性能规格表

类	描述	值
Ethernet Basic		
Jumbo Frame	Maximum jumbo frame size	9600
Unicast MAC	MAC address capacity	Default profile:122880
		IPv6 profile: 65536
		Layer3 profile: 65536
		MPLS profile: 131072
	MAC learning rate (SW)	> 4000pps
	MAC learning rate (HW)	> 10Gbps
Multicast MAC	Blackhole MAC address capacity	128
	MAC address capacity	Default profile: 2048
		IPv6 profile: 1024
		Layer3 profile: 1024
		MPLS profile: 2048

表 1: SerdesX平台性能规格表（续）

类	描述	值
Ethernet Basic		
VLAN	VLAN IDs	4094
	VLAN instances	4094
	VLANs to enable statistics	256
VLAN Mapping	Maximum mapping table	64
	Maximum rules number	3072
EVC	Maximum EVC number	4094
Link Aggregation (Static & LACP)	Maximum member number per group	No limitation
	Maximum Group Num	64
	Load balance key mode	Static/DIb/RR/Resilient/Self-healing
	Convergence time	< 50ms
VLAN Classification	Maximum rule number	4096
	Maximum group number	1
	Base MAC capacity	512
	Base IPv4 capacity	448
	Base IPv6 capacity	32
	Base protocol capacity	7
Ethernet Ring Protection		
STP	Convergence time	< 30s
RSTP	Convergence time	< 1s
MSTP	Instance number	64
	Convergence time	< 1s
ERPS	Domain number	16
	Ring number	1 Primary ring/domain 2 Sub ring/domain
	Protection instance number per Ring	64
	Switchover time	< 50 ms

表 1: SerdesX平台性能规格表（续）

类	描述	值
Ethernet OAM		
CFM (802.1ag)	Maximum session number	1024
	Maximum domain number	8
	CCM interval types	7
	CCM minimum interval	3.3ms
	Maximum down MEP number	1024
	Maximum up MEP number	1024
	Maximum LMEP number	1024
IPv4 Unicast		
ARP	ARP capacity	Default profile: 16384
		IPv6 profile: 16384
		Layer3 profile: 20480
		MPLS profile: 16384
IPv4	FIB	Default profile: 61440
		IPv6 profile: 32768
		Layer3 profile: 61440
		MPLS profile: 61440
ECMP	ECMP group	240 (Share with IPv6)
PBR	Policy route map	64
	Policy based routing ACE	1024
OSPF	Maximum static neighbors	256
	Maximum summary address	2048
IPv4 Multicast		
IPMC	Multicast routing table	Default profile: 2048
		IPv6 profile: 1024
		Layer3 profile: 2048
		MPLS profile: 1024
	Multicast routing downstream interfaces	Default profile: 4096

表 1: SerdesX平台性能规格表（续）

类	描述	值
IPv4 Multicast		
IPMC	Multicast routing downstream interfaces	IPv6 profile: 2048
		Layer3 profile: 5120
		MPLS profile: 2048
IGMP Snooping	Maximum groups number	2048
	Maximum member number	N/A
MVR	Maximum group number	Default profile: 2048
		IPv6 profile: 1024
		Layer3 Profile: 2048
		MPLS profile: 1024
	Maximum member number	Default profile: 4096
		IPv6 profile: 2048
		Layer3 profile: 5120
		MPLS profile: 2048
IPv6 Unicast		
Host Route	NDP capacity	Default profile: 2048
		IPv6 profile: 8192
		Layer3 Profile: 2048
		MPLS profile: 2048
IPv6	FIBv6	Default profile: 4096
		IPv6 profile: 16384
		Layer3 Profile: 4096
		MPLS profile: 2048
	ECMP group	240 (share with IPv4)
IPv6 Multicast		
IPMC	Multicast routing table	Default profile: 256
		IPv6 profile: 512
		Layer3 Profile: 0
		MPLS profile: 1024

表 1: SerdesX平台性能规格表（续）

类	描述	值
IPv6 Multicast		
IPMC	Number of interfaces that support Multicast routing table	Default profile: 512
		IPv6 profile: 1024
		Layer3 Profile: 0
		MPLS profile: 2048
MVR V6	Maximum entry number	Default profile: 256
		IPv6 Profile: 512
		Layer3 Profile: 0
		MPLS profile: 0
	Maximum member number	Default profile: 512
		IPv6 profile: 1024
		Layer3 Profile: 0
		MPLS profile: 0
IP tunnel		
IP Tunnel	Tunnel peer capacity	8
QoS		
Per-port Queue Number	Unicast queue	10
	Multicast queue	10
	Monitor queue	10
Packet Buffer	System packet buffer capacity	128MByte
Granularity	Policer granularity	0~2M: 10K
		2M~100M: 40K
		100M~1G: 80K
		1G~2G: 120K
		2G~4G: 250K
	Queue shape granularity	4G~10G: 500K
	Port shape granularity	10k
Flow Entry	Ingress port QoS ipv4 flow entries	1532

表 1: SerdesX平台性能规格表（续）

类	描述	值
QoS		
Flow Entry	Ingress port QoS ipv6 flow entries	1532
	Ingress port qos flow statistics entries	511
ACL		
MAC ACL	Ingress Port ACL for MAC	Default Profile: 2877
		IPv6 Profile: 2877
		Layer3 Profile: 2880
		MPLS profile: 2880
	Ingress VLAN ACL for MAC	Default Profile: 2877
		IPv6 Profile: 2877
		Layer3 Profile: 2880
		MPLS profile: 2880
	Egress Port ACL for MAC	Default Profile: 1389
		IPv6 Profile: 1389
		Layer3 Profile: 1440
		MPLS profile: 1440
	Egress VLAN ACL for MAC	Default Profile: 1389
		IPv6 Profile: 1389
		Layer3 Profile: 1440
		MPLS profile: 1440
IPv4 ACL	Ingress port ACL for IPv4	Default Profile: 2877
		IPv6 Profile: 2877
		Layer3 Profile: 2880
		MPLS profile: 2880
	Ingress VLAN ACL for IPv4	Default Profile: 2877
		IPv6 Profile: 2877
		Layer3 Profile: 2880
		MPLS profile: 2880

表 1: SerdesX平台性能规格表（续）

类	描述	值
ACL		Default Profile: 1389
		IPv6 Profile: 1389
		Layer3 Profile: 1440
		MPLS profile: 1440
IPv4 ACL	Egress port ACL for IPv4	Default Profile: 1389
		IPv6 Profile: 1389
		Layer3 Profile: 1440
		MPLS profile: 1440
IPv6 ACL	Ingress port ACL for IPv6	Default Profile: 2877
		IPv6 Profile: 2877
		Layer3 Profile: 2880
		MPLS profile: 2880
ACL Flow Statistics	Ingress ACL flow statistics entries	Default Profile: 2877
		IPv6 Profile: 2877
		Layer3 Profile: 2880
		MPLS profile: 2880

表 1: SerdesX平台性能规格表（续）

类	描述	值
ACL		
ACL Flow Statistics	Egress ACL flow statistics entries	Default Profile: 1389
		IPv6 Profile: 1389
		Layer3 Profile: 1440
		MPLS profile: 1440
CoPP	CoPP rules	1500
	CoPP flow statistics entries	1500
UDF	UDF rules	512
	UDF flow stats entries	1024
Security		
IP Source Guard	IPv4 maximum rules number	2048
	IPv6 maximum rules number	64
802.1x Base MAC	Maximum entries	512
DHCP Snooping	Maximum bound entry	4096
IPFIX		
IPFIX	IPFIX member	4096
Reliability		
BFD	Maximum session number	Share 256
S-BFD	Maximum session number	Share 256
VRRP	Maximum group number	63
Smart Link	Maximum group number	16
	Maximum instance number	64
	Switchover time	<50ms
Monitor Link	Maximum group number	16
	Maximum up-link number per group	24
Data Center		
VARP	Virtual IP number per port	15
VXLAN	VXLAN tunnel	Default Profile: 16384

表 1: SerdesX平台性能规格表（续）

类	描述	值
Data Center		
VXLAN	VXLAN tunnel	IPv6 Profile: 16384
		Layer3 Profile: 16384
		MPLS profile: 4096
	VNI	Default Profile: 4092
		IPv6 Profile: 4092
		Layer3 Profile: 4092
		MPLS profile: 2000
		Default Profile: 2048
		IPv6 Profile: 2048
	VTEP peer	Layer3 Profile: 2048
		MPLS profile: 128

SerdesX平台支持型号

表 2：SerdesX平台支持型号

系列	型号	描述
S9500	S9532-EI	32*800G OSFP， 2U， 三层以太网交换机 2*CRPS 3200W， 4*热插拔风扇模组
S8500	S8564-EI	64*400G QSFP112， 三层以太网交换机 2*CRPS 3200W， 4*热插拔风扇模组
	S8532-EI	32*400G QSFP112， 三层以太网交换机 2*CRPS 1300W， 6*热插拔风扇模组

关于HOHUNET:

HOHUNET成立于2015年，是一家专业从事开发交换机产品的技术型公司，全系列交换机均基于国产交换芯片。随着芯片技术的不断发展，HOHUNET推出了一系列基于该芯片平台的差异化产品。目前，公司产品线覆盖1G到800G，可用于企业网、运营商网、数据中心、AI计算等场景。目前公司主要合作模式为OEM/ODM，致力于为客户提供灵活的端到端定制产品和技术咨询服务。成为客户最值得信赖的商业伙伴一直是公司的使命和原则。

联系我们:

深圳市浩湖网络技术有限公司

总部地址：中国广东省深圳市南山区深南大道9996号李宁中心11楼

商务合作：business@hohunet.com

官方电话：0086-755-26418565

官方网址：www.hohunet.cn

